

	<h1 style="margin: 0;">Safety Data Sheet</h1>	<p><b>24 Hour Emergency Phone Numbers</b>  <b>Medical/Poison Control:</b>                  In U.S.: Call 1-800-222-1222</p> <p><b>Outside U.S.: Call your local poison control center</b></p> <p><b>Transportation/National Response Center:</b></p> <p style="text-align: center;">1-800-535-5053 1-352-323-3500</p> <p><small>NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.</small></p>
---	---	---

**IMPORTANT:** Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

## 1. Identification

<b>Product Name:</b>	Weldwood Multi Purpose Spray Adhesive	<b>Revision Date:</b>	4/18/2024
<b>Product UPC Number:</b>	070798001244	<b>Supercedes Date:</b>	3/15/2024
<b>Manufactured For</b>	DAP Global Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	<b>Product Use/Class:</b>	Adhesive
	SDS Coordinator: MSDS@dap.com	<b>SDS No:</b>	3042704
	Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222	<b>Preparer:</b>	Regulatory and Environmental Affairs

## 2. Hazards Identification

**EMERGENCY OVERVIEW:** CAUTION! Avoid breathing vapor. Avoid skin and eye contact. Use only with adequate ventilation. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Irritating to eyes, respiratory system and skin. Harmful or fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage. Contents under pressure. Do not puncture can. Exposure to temperatures above 120 °F may cause can to rupture. May affect the brain or nervous system causing dizziness, headache or nausea.

**GHS Classification**

Carc. 2, Eye Irrit. 2A, Fl Aer, 1, Gas under Pressure, Comp. Gas, Repr. 2, STOT RE 2, STOT SE 3 NE

**Symbol(s) of Product****Signal Word**

Danger

**Possible Hazards**

72% of the mixture consists of ingredients of unknown acute toxicity

**GHS HAZARD STATEMENTS**

Flammable Aerosol, category 1	H222	Extremely flammable aerosol.
Compressed Gas	H280	Contains gas under pressure; may explode if heated.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.

**GHS LABEL PRECAUTIONARY STATEMENTS**

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
P501	Dispose of contents/container.

**3. Composition/Information on Ingredients**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Acetone	67-64-1	30-60	GHS02-GHS07	H225-319-336
Propane	74-98-6	10-30	GHS07	H332-336
Rosin pentaerythrityl ester, hydrogenated	64365-17-9	7-13	No Information	No Information
Isobutane	75-28-5	5-10	GHS02-GHS07	H220-332-336
Toluene	108-88-3	3-7	GHS02-GHS07-GHS08	H225-304-315-320-332-335-336-351-361-372
Dipropylene glycol dibenzoate	27138-31-4	1-5	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures

**FIRST AID - INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. NOTE: Only trained personnel should administer artificial respiration or give oxygen.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist. Remove and wash contaminated clothing. DO NOT try to peel the solidified material from the skin or use solvents or thinners to dissolve it. The use of vegetable oil or mineral oil is recommended for removal of this material from the skin. Flush exposed area with water while removing contaminated clothing. Get medical attention if irritation persists. To remove from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.

**FIRST AID - EYE CONTACT:** If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

**FIRST AID - INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

## 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Containers may explode if exposed to extreme heat.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces. Cool fire-exposed containers using water spray.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

## 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

## 7. Handling and Storage

**HANDLING:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Make sure nozzle is directed away from yourself prior to discharge. Use in well ventilated area. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Empty containers retain product residue (liquid and/or vapor). Vapor can ignite potentially causing an explosion. Do not use in areas where static sparks may be generated. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. Construction and repair activities can adversely affect indoor air quality. Consult with occupants or a representative (i.e. maintenance, building manager, industrial hygienist, or safety officer) to determine ways to minimize impact.

**STORAGE:** Store away from sources of ignition and heat. Keep away from heat and sources of ignition. Protect material from direct sunlight. Do not store at temperatures above 120 °F (49 °C). Store containers away from excessive heat and freezing. Store away from caustics and oxidizers. Keep containers tightly closed.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Acetone	250 ppm TWA	500 ppm STEL	1000 ppm TWA, 2400 mg/m <sup>3</sup> TWA	N.E.
Propane	See Appendix F: Minimal Oxygen Content, explosion hazard	N.E.	1000 ppm TWA, 1800 mg/m <sup>3</sup> TWA	N.E.
Rosin pentaerythryl ester, hydrogenated	N.E.	N.E.	N.E.	N.E.
Isobutane	N.E.	1000 ppm STEL explosion hazard	N.E.	N.E.
Toluene	20 ppm TWA	N.E.	200 ppm TWA	300 ppm Ceiling
Dipropylene glycol dibenzoate	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

## Personal Protection



**RESPIRATORY PROTECTION:** A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits. If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear and appropriate, properly fitted respirator (NIOSH approved) during and after application. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



**SKIN PROTECTION:** Solvent-resistant gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



**OTHER PROTECTIVE EQUIPMENT:** Provide eyewash and solvent impervious apron if body contact may occur.



**HYGIENIC PRACTICES:** Remove and wash contaminated clothing before re-use.

## 9. Physical and Chemical Properties

Color:	Tan	Appearance:	Aerosol
Odor:	Solvent	Physical State:	Aerosol
Density, g/cm <sup>3</sup> :	0.75	Odor Threshold:	Not Established
Freeze Point, °C:	Not Established	pH:	Not Applicable
Solubility in Water:	Not Established	Viscosity (mPa.s):	Not Applicable
Decomposition Temperature, °C:	Not Established	Partition Coeff., n-octanol/water:	Not Established
Boiling Range, °C:	N.A. Aerosol, foam.	Explosive Limits, %:	N.E.
Flash Point, °C:	Aerosol or foam, not applicable.	Auto-Ignition Temperature, °C	Not Established
Evaporation Rate:	Faster Than n-Butyl Acetate	Vapor Pressure, mmHg:	Not Established
Vapor Density:	Heavier Than Air	Flash Method:	Not Applicable
Combustible Dust:	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Do not burn or use a cutting torch on the empty container. Excessive heat or flames, incompatible substances. Keep away from open flames, hot surfaces and sources of ignition. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Avoid contact with skin, eyes and clothing. Do not smoke.

**INCOMPATIBILITY:** Exothermic reaction with strong acids. Strong oxidizing agents. Strong bases.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Normal decomposition products, i.e., CO<sub>x</sub>, NO<sub>x</sub>.

## 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation of vapors may cause irritation of the nose, throat, lungs and respiratory tract. Inhalation of vapors in high concentration may cause shortness of breath (lung edema). Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Prolonged, repeated or high exposures may cause central nervous system depression leading to headaches, nausea, drowsiness, dizziness, and possibly narcosis. In extreme cases, may cause loss of consciousness.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Harmful if absorbed through the skin. May cause skin irritation. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** May cause eye irritation. Signs and symptoms may include: pain, tears, swelling, redness and blurred vision.

**EFFECT OF OVEREXPOSURE - INGESTION:** Harmful or fatal if swallowed. May cause gastrointestinal disturbances with dizziness and central nervous system depression. If ingested, may cause depressed respiration. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal.

**CARCINOGENICITY:** No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated or prolonged exposure may cause irregular heartbeat and heart failure as well as respiratory system, kidney, cardiovascular and liver damage. May cause kidney and liver damage as well as developmental and reproductive toxicity. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability and loss of coordination. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Overexposure or misuse of toluene can cause liver, kidney, and brain damage as well as cardiac abnormalities. There have been cases of aplastic anemia from toluene in industrial exposures (ACGIH, 1992). Increased coagulation time and reduced clotting factors have also been found, which are indicators of damage to the bone marrow (Clayton & Clayton, 1994). Symptoms include: loss of memory, loss of intellectual ability and loss of coordination.

**PRIMARY ROUTE(S) OF ENTRY:** Skin Contact, Inhalation, Eye Contact

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
67-64-1	Acetone	5250 mg/kg mouse	>15688 mg/kg rabbit	50 mg/L Rat
74-98-6	Propane	Not an exposure route	Not an exposure route	N.I.
64365-17-9	Rosin pentaerythrityl ester, hydrogenated	10000 mg/kg Rat	5000 mg/kg Rabbit	N.I.
75-28-5	Isobutane	N.I.	N.I.	N.I.
108-88-3	Toluene	2600 mg/kg Rat	12000 mg/kg Rabbit	12.5 mg/L Rat
27138-31-4	Dipropylene glycol dibenzoate	3914 mg/kg Rat	>2000 mg/kg Rat	N.I.

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Residues and spilled material are hazardous waste due to ignitability. Contents under pressure. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Do not flush into surface water or sanitary sewer system. Do not empty into drains. Do not re-use empty containers. The container for this product can present explosion or fire hazards, even when emptied. To avoid risk of injury, do not cut, puncture, or weld on or near this container. Before disposing of containers, relieve container of any remaining product and pressure. Empty cylinders, once relieved of all pressure, can be disposed of as non-hazardous waste.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal

regulations. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

## 14. Transport Information

DOT UN/NA Number: UN1950  
 DOT Proper Shipping Name: Aerosols, flammable  
 DOT Technical Name: N.A.  
 DOT Hazard Class: 2.1 Flammable gas  
 Hazard SubClass: N.A.  
 Packing Group: N.A.

SPECIAL TRANSPORT PRECAUTIONS: No Information

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Gas under pressure, Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Toluene	108-88-3

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

**16. Other Information**

**Revision Date:** 4/18/2024 **Supersedes Date:** 3/15/2024

**Reason for revision:** Product Composition Changed  
 Substance and/or Product Properties Changed in Section(s):  
 02 - Hazards Identification  
 09 - Physical & Chemical Information  
 11 - Toxicological Information  
 15 - Regulatory Information  
 Revision Statement(s) Changed

**Datasheet produced by:** Regulatory Department

**HMIS Ratings:**

Health:	Flammability:	Reactivity:	Personal Protection:
3*	4	0	X

VOC Less Water Less Exempt Solvent, g/L: 396.7

VOC Material, g/L: 223

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 29.56

VOC Actual, Wt/Wt%: 29.6

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H320 Causes eye irritation
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

- GHS02 
- GHS07 
- GHS08 

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

We believe the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.