



## Safety Data Sheet

**24 Hour Emergency Phone Numbers**  
**Medical/Poison Control:**  
 In U.S.: Call 1-800-222-1222

**Outside U.S.: Call your local poison control center**

**Transportation/National Response Center:**

**1-800-535-50531-3**  
**52-323-3500**

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

**IMPORTANT:** Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

### 1. Identification

<b>Product Name:</b>	Weldwood Original Contact Cement	<b>Revision Date:</b>	4/12/2022
<b>Product UPC Number:</b>	070798002715, 070798002722, 070798002739	<b>Supercedes Date:</b>	12/29/2021
<b>Manufacturer:</b>	DAP Global Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	<b>Product Use/Class:</b>	Adhesive
	SDS Coordinator: MSDS@dap.com	<b>SDS No:</b>	3050301
	Emergency Telephone: Transportation: 1-800-535 -5053 1-352-323-3500 Poison Control: 1-800-222-1222	<b>Preparer:</b>	Regulatory and Environmental Affairs

### 2. Hazards Identification

**EMERGENCY OVERVIEW:** DANGER! Flammable liquid and vapor. Vapors may cause flash fire or explosion. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Flammable liquid and vapor. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Keep container closed and away from heat, sparks, and open flame. Store away from caustics and oxidizers. Avoid breathing vapor. Avoid skin and eye contact. Use only with adequate ventilation. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Irritating to eyes, respiratory system and skin. Harmful or fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage. May affect the brain or nervous system causing dizziness, headache or nausea.

**GHS Classification**

Acute Tox. 4 Inhalation, Carc. 1B, Eye Irrit. 2, Flam. Liq. 2, Muta. 1B, Skin Irrit. 2, STOT RE 2, STOT SE 3 NE, STOT SE 3 RTI

**Symbol(s) of Product****Signal Word**

Danger

**Possible Hazards**

21% of the mixture consists of ingredients of unknown acute toxicity

**GHS HAZARD STATEMENTS**

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Germ Cell Mutagenicity, category 1B	H340	May cause genetic defects .
Carcinogenicity, category 1B	H350	May cause cancer.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.

**GHS LABEL PRECAUTIONARY STATEMENTS**

P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P321	Specific treatment (see ... on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P370+P378	In case of fire: Use... to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container.

**GHS SDS PRECAUTIONARY STATEMENTS**

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

**3. Composition/Information on Ingredients**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Toluene	108-88-3	30-60	GHS02-GHS07-GHS08	H225-304-315-332-335-336-373
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	10-30	GHS07-GHS08	H304-312-315-332-336-340-350
Methyl ethyl ketone (MEK)	78-93-3	7-13	GHS02-GHS07	H225-319-332-336
Petroleum hydrocarbon resin	64742-16-1	1-5	No Information	No Information
Magnesium oxide	1309-48-4	0.5-1.5	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

#### 4. First-aid Measures

**FIRST AID - INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. NOTE: Only trained personnel should administer artificial respiration or give oxygen.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist. Remove and wash contaminated clothing. DO NOT try to peel the solidified material from the skin or use solvents or thinners to dissolve it. The use of vegetable oil or mineral oil is recommended for removal of this material from the skin. Flush exposed area with water while removing contaminated clothing. Get medical attention if irritation persists. To remove from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.

**FIRST AID - EYE CONTACT:** If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

**FIRST AID - INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

#### 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Eliminate sources of ignition: heat, electrical equipment, sparks and flames. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Vapors may form explosive mixtures with air. Containers may explode if exposed to extreme heat. Empty containers retain product residue (liquid and/or vapor). Vapor can ignite potentially causing an explosion.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces. Cool fire-exposed containers using water spray.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

#### 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

#### 7. Handling and Storage

**HANDLING:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Remove all sources of ignition. Keep away from open flames, hot surfaces and sources of ignition. Provide adequate ventilation. Avoid heat, sparks and open flames. Wear appropriate personal protection. Avoid breathing vapor and contact with eyes, skin and clothing. Use in well ventilated area. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Empty containers retain product residue (liquid and/or vapor). Vapor can ignite potentially causing an explosion. Wash thoroughly after handling. Do not use in areas where static sparks may be generated. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. Construction and repair activities can adversely affect indoor air quality. Consult with occupants or a representative (i.e. maintenance, building manager, industrial hygienist, or safety officer) to determine ways to minimize impact.

**STORAGE:** Store away from sources of ignition and heat. Do not store at temperatures above 120 °F (49 °C). Store containers away from excessive heat and freezing. Store away from caustics and oxidizers. Keep containers tightly closed.

#### 8. Exposure Controls/Personal Protection

##### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Toluene	20 ppm TWA	N.E.	200 ppm TWA	300 ppm Ceiling

Distillates (petroleum), light distillate hydrotreating process, low-boiling Methyl ethyl ketone (MEK)	N.E.	N.E.	N.E.	N.E.
	200 ppm TWA	300 ppm STEL	200 ppm TWA, 590 mg/m <sup>3</sup> TWA	N.E.
Petroleum hydrocarbon resin	N.E.	N.E.	N.E.	N.E.
Magnesium oxide	10 mg/m <sup>3</sup> TWA inhalable particulate matter	N.E.	15 mg/m <sup>3</sup> TWA fume, total particulate	N.E.

**Further Advice:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

## Personal Protection



**RESPIRATORY PROTECTION:** A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits. If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear and appropriate, properly fitted respirator (NIOSH approved) during and after application. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



**SKIN PROTECTION:** Solvent-resistant gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



**OTHER PROTECTIVE EQUIPMENT:** Provide eyewash and solvent impervious apron if body contact may occur.



**HYGIENIC PRACTICES:** Remove and wash contaminated clothing before re-use.

## 9. Physical and Chemical Properties

<b>Color:</b>	No Information	<b>Appearance:</b>	Tan
<b>Odor:</b>	Strong Solvent	<b>Physical State:</b>	Thick Liquid
<b>Density, g/cm<sup>3</sup>:</b>	0.88 - 0.88	<b>Odor Threshold:</b>	Not Established
<b>Freeze Point, °C:</b>	Not Established	<b>pH:</b>	Not Applicable
<b>Solubility in Water:</b>	Not Established	<b>Viscosity (mPa.s):</b>	Not Established
<b>Decomposition Temperature, °C:</b>	Not Established	<b>Partition Coeff., n-octanol/water:</b>	Not Established
<b>Boiling Range, °C:</b>	76.7 - 82.2	<b>Explosive Limits, %:</b>	N.E.
<b>Flash Point, °C:</b>	-6.1	<b>Auto-Ignition Temperature, °C</b>	Not Established
<b>Evaporation Rate:</b>	Not Established	<b>Vapor Pressure, mmHg:</b>	Not Established
<b>Vapor Density:</b>	Not Established	<b>Flash Method:</b>	Pensky-Martens Closed Cup
<b>Combustible Dust:</b>	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Keep away from open flames, hot surfaces and sources of ignition. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Avoid contact with skin, eyes and clothing. Do not smoke.

**INCOMPATIBILITY:** Open flames, hot surfaces and sources of ignition. Keep away from strong oxidizing agents, heat and open flames. Exothermic reaction with strong acids. Strong oxidizers, alkali metals and alkaline earth metals may cause fires or explosions.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Normal decomposition products, i.e., COx, NOx.

## 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation of vapors may cause irritation of the nose, throat, lungs and respiratory tract. Inhalation of vapors in high concentration may cause shortness of breath (lung edema). Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Prolonged, repeated or high exposures may cause central nervous system depression leading to headaches, nausea, drowsiness, dizziness, and possibly narcosis. In extreme cases, may cause loss of consciousness.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Harmful if absorbed through the skin. May cause skin irritation. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** May cause eye irritation. Signs and symptoms may include: pain, tears, swelling, redness and blurred vision.

**EFFECT OF OVEREXPOSURE - INGESTION:** Harmful or fatal if swallowed. May cause gastrointestinal disturbances with dizziness and central nervous system depression. If ingested, may cause depressed respiration. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal.

**CARCINOGENICITY:** No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated or prolonged exposure may cause skin, respiratory, kidney and liver damage. May cause kidney and liver damage as well as developmental and reproductive toxicity. Prolonged or repeated inhalation of solvent vapors may cause irregular heartbeat. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability and loss of coordination. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Overexposure or misuse of toluene can cause liver, kidney, and brain damage as well as cardiac abnormalities. There have been cases of aplastic anemia from toluene in industrial exposures (ACGIH, 1992). Increased coagulation time and reduced clotting factors have also been found, which are indicators of damage to the bone marrow (Clayton & Clayton, 1994). Symptoms include: loss of memory, loss of intellectual ability and loss of coordination.

**PRIMARY ROUTE(S) OF ENTRY:** Skin Contact, Skin Absorption, Inhalation

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
108-88-3	Toluene	2600 mg/kg Rat	12000 mg/kg Rabbit	12.5 mg/L Rat
68410-97-9	Distillates (petroleum), light distillate hydrotreating process, low-boiling	5170 mg/kg Rat	1900 mg/kg Rabbit	N.I.
78-93-3	Methyl ethyl ketone (MEK)	2483 mg/kg Rat	5000 mg/kg Rabbit	34.5 mg/l Rat
64742-16-1	Petroleum hydrocarbon resin	N.I.	N.I.	N.I.
1309-48-4	Magnesium oxide	>3870 mg/kg Rat	N.I.	N.I.

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Residues and spilled material are hazardous waste due to ignitability. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Liquids cannot be disposed of in a

landfill. Do not flush into surface water or sanitary sewer system. Do not empty into drains. Do not re-use empty containers. The container for this product can present explosion or fire hazards, even when emptied. To avoid risk of injury, do not cut, puncture, or weld on or near this container.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

## 14. Transport Information

**DOT UN/NA Number:** UN1133  
**DOT Proper Shipping Name:** Adhesives, containing a flammable liquid  
**DOT Technical Name:** N.A.  
**DOT Hazard Class:** 3 Flammable liquid  
**Hazard SubClass:** N.A.  
**Packing Group:** III

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Toluene	108-88-3

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

**16. Other Information**

**Revision Date:** 4/11/2022 **Supersedes Date:** 12/29/2021

**Reason for revision:** Substance and/or Product Properties Changed in Section(s):  
01 - Product Information

**Datasheet produced by:** Regulatory Department

**HMIS Ratings:**

<b>Health:</b>	<b>Flammability:</b>	<b>Reactivity:</b>	<b>Personal Protection:</b>
3*	3	1	X

**VOC Less Water Less Exempt Solvent, g/L:** 710.1

**VOC Material, g/L:** 709

**VOC as Defined by California Consumer Product Regulation, Wt/Wt%:** 66.85

**VOC Actual, Wt/Wt%:** 80.4

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.