



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Liquid Cement Crack Filler

PRODUCT DESCRIPTION

DAP® Liquid Cement Crack Filler is an easy-to-use, ready mixed product for the repair of horizontal concrete cracks. Repairs are ready for traffic 30-45 minutes following application, when directions are properly followed. Liquid Cement is self-leveling and dries gray to match most existing concrete.

NOTE: Fills cracks up to ½" in width. For cracks greater than ½" in width, use DAP Ready-Mixed or Dry Mix Concrete Patch.



PACKAGING	COLOR	UPC
Quart	Light Grey	7079837584

KEY FEATURES & BENEFITS

- Repairs cracks and surface defects in concrete
- Self-leveling
- Easy to use, ready-mixed formula

SUGGESTED USES

It is ideal for filling and repairing concrete and cement cracks.

APPLICATION

1. Do not use if temperature is below 45°F (7°C), or if rain is likely. Keep product from freezing. Always wear rubber gloves and eye protection.
2. Clean all foreign material from crack, Liquid Cement must be applied to a clean, dry and sound surface.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

3. Shake Liquid Cement bottle prior to opening and before each use to ensure consistent mixture. Bottle nozzle should be snipped with scissors to initially open. (The product will flow faster if the bottle is set into hot water for 10 minutes prior to use in cooler temperature conditions).
4. Fill crack in ¼ inch layers allowing at least 24 hours between applications.
5. For very thin cracks, Liquid Cement may be “pressed” or troweled flat into and around crack.
6. Product may be painted with latex or oil-based paints

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Appearance/Consistency	Liquid
Color	Light Gray
Set Time	24 hours
Shelf Life	12 months
Application Temperature	Apply in temperatures above 40°F

CLEAN UP & STORAGE

Clean up wet material with soap and water. Dried material must be cut or scraped away. Close container tightly and store in a cool, dry place. Keep from freezing.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com